



Model	AUG15-K	AUG15-P	AUG15-F	AUG15-L
PrimePower(kw)	15			
RatedVoltage(V)	415			
RatedFrequency(Hz)	50			
Dimension (L*W*H) mm	1430 * 1560* 940			
Weight(kg)	850			
Fuel tank capacity(L)	200			
<b>Diesel Engine</b>				
Model	V2203	404D-22G	4DW91-29D	4L22BD
Manufacturer	Kubota	Perkins	FAW	Laidong
Type	Vertical, 4-cycle, water-cooled diesel engine			
Intake Method	Natural aspirated			
Rated speed	1800 r/min			
Rated output(kw)	24.2	23.9	21	23.1
Cylinder Number	4	4	4	4
Bore (mm)	87	84	90	85
Stroke(mm)	92.4	100	100	95
Displacement(L)	2.197	2.216	2.54	2.156
Compression Ratio	23	23.3	18.5	23.3
Fuel consumption	1.5 ~ 2.5 L/h (Loading reefer container)			
<b>Alternator</b>				
Model	RF4-20			
Manufacturer	XIAMEN AI POWER TECHNOLOGY CO., LTD.			
Exciting mode	PMG			
Insulation Grade	H			
Enclosure Grade	IP55			
<b>Control System</b>				
Control module	Deepsea 3110			
Instrument	Temperature gauge, Oil pressure gauge, on/off switch			
Protection feature	Over/under voltage, over/under frequency, over load, short circuit, Low Oil Pressure, High Water Temperature, Low Fuel Level, Charging Failure, Over Speed, etc			
<b>Auxiliary System</b>				
Battery	12V DC Free Maintenance Battery			
Auxiliary sockets	1x32Amp			
FuelLevelGauge	Mechanical Fuel Level Gauge			