



Model	AUG15-L
PrimePower(kw)	15
RatedVoltage(V)	415
RatedFrequency(Hz)	50
Dimension (L*W*H) mm	1430 * 1560* 940
Weight(kg)	850
Fuel tank capacity(L)	200
Diesel Engine	
Model	4L22BD
Manufacturer	Laidong
Type	Vertical, 4-cycle, water-cooled diesel engine
Intake Method	Natural aspirated
Rated speed	1800 r/min
Rated output(kw)	23.1
Cylinder Number	4
Bore (mm)	85
Stroke(mm)	95
Displacement(L)	2.156
Compression Ratio	23.3
Fuel consumption	1.5 ~ 2.5 L/h (Loading reefer container)
Alternator	
Model	LSA40M5
Manufacturer	LeroySomer
Exciting mode	Shunt
Insulation Grade	H
Enclosure Grade	IP23
Control System	
Control module	Deepsea 3110
Instrument	Temperature gauge, Oil pressure gauge, on/off switch
Protection feature	Over/under voltage, over/under frequency, over load, short circuit, Low Oil Pressure, High Water Temperature, Low Fuel Level, Charging Failure, Over Speed, etc
AuxiliarySystem	
Battery	12V DC Free Maintenance Battery
Auxiliary sockets	1x32Amp
FuelLevelGauge	Mechanical Fuel Level Gauge